

Traditional extraction apparatus



Application

Extractions according to Soxhlet, Twisselmann and other techniques.

Available models

Serial heating unit with 4 or 6 individually adjustable heating places for flasks of 250 - 500 ml. Supplied with top moulds, air bath inserts, support rods (600 mm x 12 mm) and power cord.

- EV6 All/14 Extraction apparatus (Soxhlet), 4-place, 230 VAC 50-60 Hz, order no. 10-0011
- EV6 All/16 Extraction apparatus (Soxhlet), 6-place, 230 VAC 50-60 Hz, order no. 10-0012

Accessories for extraction heating units

- Holder with fixed clamp to attach Soxhlet glass parts on support rod, order no. 10-0054
- Cooling water feed pipe for four-place extraction heating unit, order no. 10-0059
- Cooling water feed pipe for six-place extraction heating unit, order no. 10-0060
- Set of Soxhlet glass parts consisting of 1 flat-bottom flask (500 ml), 1 extractor (180 ml), and 1 Dimroth condenser, order no. 10-0061
- Extraction thimbles, 33 x 80 mm (25 pieces), order no. 13-0054

Information on our rapid extraction systems SOXTHERM with fully automated extraction process and comprehensive safety features can be obtained



Postbus 2151 Pascallaan 9
8203 AD Lelystad 8218 NJ Lelystad
Tel: 0320-266171 Fax: 0320-257354
email: laboratorium@dijkstra.net
www.dijkstra.net