

## Data Sheet

Analytical line / Calorimeters



**dijkstra  
vereenigde**

Postbus 2151      Pascallaan 9  
8203 AD Lelystad      8218 NJ Lelystad  
Tel: 0320-266171      Fax: 0320-257354  
email: [laboratorium@dijkstra.net](mailto:laboratorium@dijkstra.net)  
[www.dijkstra.net](http://www.dijkstra.net)

### C 7000 basic equipment set 1

The C 7000 is the first IKA® calorimeter with a completely dry system for measuring the gross calorific value of solid and liquid samples. The temperature is measured directly in the decomposition system. This results in measurement times in the range of 3 to 7 minutes (depending on the sample). The system can manage up to 8 different decomposition vessels using a code ring scheme.

- High sample frequency
- Precise and reproducible determination of gross calorific values according to ISO 1928
- Reduction of routine work through automatic application flow
- Automatic decomposition vessel identification
- Interface connections for scale, printer and PC
- User-friendly software C 5040 CalWin for controlling the calorimeter and administration of measuring data
- The decomposition vessel can be changed over to use combustible crucibles C 14

C 7000 basic equipment set 1 consisting of:

- C 7000 Measurement cell
- C 7010 Decomposition vessel, standard
- C 7002 Cooling system
- C 48 Oxygen station

Accessories: C 7010 Decomposition vessel, standard, C 7012 Decomposition vessel, halogen resistant, C 5010.4 Attachment for combustible crucible C14, C 5010.5 Crucible holder, big, C 7010.8 Venting handle, C 7030 Venting station, C 5040 CalWin, C 5041.10 Connection cable, C 7002 Cooling system (230V), KV 600 cooling water supply, C 21 Pelleting press, C 48 Oxygen station, C 29 Pressure gauge, oxygen, C 5003.1 Aqua Pro stabilizing agent, C 710.4 Cotton thread, cut to length, C 10 Acetobutyrate capsules, C 5010.3 Ignition wire, spare, C 5012.3 Ignition wire, platinum, C 4 Quartz dish, C 6 Quartz crucible, big, C 5 Set of VA combustion crucibles, C 710.2 Set of VA combustion crucibles, C 723 Benzoic acid, blister package, C 723 Benzoic acid BIG Package, C 43 Benzoic acid NBS 39i, C 9 Gelatine capsules, C 12 Combustion bags 40 x 35 mm, C 12 A Combustion bags 70 x 35 mm, C 14 Combustible crucible, C 15 Paraffin strips, C 16 Parafilm, C 17 Paraffin, AOD 1.11 Control standard, AOD 1.12 Control standard

#### Technical Data

Measuring range max. [J]	30000
Measuring mode double dry (ISO 1928)	yes
Measuring time double dry approx. [min]	3
Double dry reproducibility (1g benzoic acid NBS39i) [%RSD]	0.2
Working temperature max. [°C]	30
Temperature measurement resolution [K]	0.0001
Cooling medium temperature min. [°C]	12
Cooling medium temperature max. [°C]	30
Cooling medium permissible operating pressure [bar]	9
Cooling medium	tap water
Type of cooling	flow
Flow rate min. [l/h]	120
Flow rate max. [l/h]	180
Oxygen operating pressure max. [bar]	40
Interface scale	RS232
Interface printer	Centronix
Interface PC	RS232
Oxygen filling	no
Degasification	no
Decomposition detection	yes
Decomposition vessel C 7010	yes
Dimensions (W x H x D) [mm]	310 x 395 x 490
Weight [kg]	43
Permissible ambient temperature [°C]	18 - 30
Permissible relative moisture [%]	80
RS 232 interface	yes
Voltage [V]	220 - 240
Frequency [Hz]	50/60
Power input [W]	260
<b>Ident. No.</b>	<b>8800900</b>