

## Data Sheet

Mixing / Overhead Stirrers



Postbus 2151 Pascallaan 9  
 8203 AD Lelystad 8218 NJ Lelystad  
 Tel: 0320-266171 Fax: 0320-257354  
 email: laboratorium@dijkstra.net  
 www.dijkstra.net

## EUROSTAR power control-visc P7

Laboratory stirrer with a high torque, 7-fold transmission reduction for processing highly viscous media.

- Constant speed by microprocessor control
- Digital display presents rated - / actual speed
- Infinitely adjustable without gear shifting
- Slim casing
- Quiet operation
- Safety circuit
- Non-locking, overload capabilities
- Enhanced safety as a result of smooth start
- Integrated torque trend display for viscosity control
- Analog interface for recording speed and torque
- RS 232 interface
- Agitator shafts are not push-through

Accessories: R 1385 Propeller stirrer, 3-bladed, RH 5 Strap clamp, R 1342 Propeller stirrer, 4-bladed, R 1330 Anchor stirrer, R 1312 Turbine stirrer, R 301 Stirring shaft protection, R 271 Boss head clamp, labworldsoft®, R 1345 Propeller stirrer, 4-bladed, R 1375 Paddle stirrer, R 1376 Paddle stirrer, R 1382 Propeller stirrer, 3-bladed, R 1381 Propeller stirrer, 3-bladed, R 2722 H-Stand, R 2723 Telescopic stand, R 1331 Anchor stirrer, R 1311 Turbine stirrer, R 1313 Turbine stirrer, R 1389 (PTFE-coated) Propeller stirrer, 3-bladed, R 1333 Anchor stirrer, R 1388 Propeller stirrer, 3-bladed

Technical Data	
Stirring quantity max. (H <sub>2</sub> O) [l]	40
Motor rating input [W]	130
Motor rating output [W]	110
Speed display	LCD
Speed range [rpm]	8 - 290
Viscosity max. [mPas]	150000
Output max. at stirring shaft [W]	95
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	380
Torque max. at stirring shaft at 60 1/min (overload) [Ncm]	380
Torque max. at stirring shaft at 100 1/min [Ncm]	380
Torque max. at stirring shaft at 1.000 1/min [Ncm]	380
Speed control	stepless
Stirring element fastening	chuck
Chuck range min. diameter [mm]	0.5
Chuck range max. diameter [mm]	10
Hollow shaft (push-through $\checkmark$ when stopped)	none
Fastening on stand	extension arm
Extension arm diameter [mm]	16
Extension arm length [mm]	200
Torque display	yes
Nominal torque [Nm]	3.8
Torque measurement	trend
Dimensions (W x H x D) [mm]	80 x 330 x 190
Weight [kg]	4.9
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	yes
Analog output	yes
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	130
<b>Ident. No.</b>	<b>2850700</b>